

# TP12



## TP12 Bulk pallet unitizer for cans

### Optimizes Performance

Equalized strap tension ensures maximum load stability

### Streamlines Operation

Innovative features to reduce downtime

### Cost-efficient Design

Built with fewer parts to maximize machine longevity

### Innovative Construction

Modular design simplifies upkeep

# TP12

## Bulk pallet unitizer for cans



The TP12 provides consistent, retained strap tension to eliminate loose straps, maximizing load stability throughout the distribution cycle. Built with features that facilitate easier maintenance and operation, the TP12 provides the lowest cost of ownership available.

### Features and benefits

#### ■ Unparalleled package performance

The TP12's innovative tensioning system equalizes strap tension from both the top and bottom, providing the most accurate, consistent tension levels to ensure load stability.

#### ■ Quick-change technology

Constructed with separate, lightweight tensioning and sealing components, the TP12 strapping head modules are easy to access and remove for maintenance, drastically reducing downtime for routine maintenance. They are built with fewer moving parts and more durable wear parts, making them easier and more cost-efficient to maintain than traditional strapping heads.



Tensioning module

Sealing module

### TP12 options

- Spare modular head set
- Strap applied switch
- Indicator light
- Out-of-strap switch
- Conveyor height



### TP12 Technical Specifications

<b>Load Height Minimum</b>	711 mm (28")
<b>Load Height Maximum</b>	2870 mm (113")
<b>Load Width Minimum</b>	762 mm (30")
<b>Load Width Maximum</b>	1524 mm (60")
<b>Strap Requirements</b>	1614 Tenax polyester strapping
<b>Conveyor Height</b>	Adjustable 127 – 508 mm (5"-20")
<b>Electrical</b>	460 volts, 60 Hz, 3 phase
<b>Shipping Weight</b>	590 kg to 953 kg (1,300 lbs to 2,100 lbs) depending on model

